



CARRIAGEWAY KEY

- Plane carriageway 45mm deep and resurface with (45mm thick) HRA 35/14 F surface course 40/60 (Clause 910) with 20mm coated chippings (Min PSV 68).
- As surrounding construction, apply High Friction Surface Treatment (70 PSV) (Charcoal In Colour).

NOTES

- Take up and replace and or adjust existing Ironwork as detailed in the schedule.
- Road markings to be replaced as detailed in the road marking schedule.
- Traffic Management to comply with requirements of Chapter 8 & Diversion Drawings.
- Refer to the patching schedule for proposed 55mm thick AC 20 Dense Bin 40/60 (Clause 906 Recipe Mix). The Engineer may identify additional binder patching works following planning.
- Construction Completion Date:

Section	Timing	C/W Widths	Traffic Man.
CH 0.00 - 87.00	Daytime Working 0930 -1600hrs	Min = 10.1m Max = 10.2m	2 /3Way Lights &TM Marshalls 30mph & 10 speed order & speed camera signs
CH87.00 - 720.6	Daytime Working 0930 -1600hrs	Min = 10.0m Max = 10.2m	Lane Closure & one way diversion. TM Marshalls 30mph & 10 speed order & speed camera signs

AMENDMENT DETAILS			
BY	CHNO	AP/D	DATE

DERBYSHIRE County Council
Improving life for local people

MIKE ASHWORTH
 Strategic Director – Economy, Transport and Environment

HIGHWAYS MANAGEMENT

BSI ISO 5001 Quality Management
 FMS41223 / FMS41224

DRAWN R.M.PITCHFORK	CHECKED M.WRIGHT	APPROVED R.MOORE
Date 22/06/2017	Date 27/06/2017	Date 27/06/2017
PROJECT TITLE A632 SLACK HILL ASHOVER CARRIAGEWAY RESURFACING SCHEME		
DRAWING TITLE CONSTRUCTION DRAWING (CARRIAGEWAY)		
DCE Project Reference No. 17-0003-01-05	SCALE N.T.S	
Drawing Number 17-0003-01-05/RMP/02		

© Crown Copyright and database rights (2016). Ordnance Survey (100023251).
 You are not permitted to copy, sub-licence, distribute or sell any of this data to third parties in any form.